



VIVID audio

GIYA G4

SERIES 2

The G4 packs all the unique features of the Giya principles into an enclosure just 1m in height. It embodies all the essential features without compromise and delivers a result that is completely worthy of carrying the name of Giya.



GIYA G4

A masterpiece resized

Exceptional purity through the mid and high frequencies is assured by the combination of the D50 and D26 aluminium magnesium alloy and carbon fibre dome drivers. These two units deliver a high frequency performance to well beyond the range of human hearing.

Specification

Configuration	4 way 5 driver system
Cabinet material	Glass reinforced balsa cored sandwich composite
Standard cabinet colour	Multi component high gloss automotive
Bespoke cabinet colour	Bespoke colour options available on request
Drive units	HF: D26—26mm metal dome unit with Tapered Tube loading Mid: D50—50mm metal dome unit with Tapered Tube loading Lower Mid: C100S—100mm metal coned driver with Tapered Tube loading LF: C125L—2 x alloy cone units with short-coil long-gap motor design
Bass loading	Exponentially tapered tube enhanced bass reflex
Sensitivity	86dB @ 2.83Vrms at 1.0 meter on axis
Nominal impedance (Ω)	6 nominal, 4 minimum, low reactance
Frequency range (Hz)	- 6 dB points: 36–36,000 Hz
First D26 Break Up mode	44,000 Hz
Frequency response	39–33,000 +/- 2 dB on reference axis
Harmonic distortion (2nd and 3rd harmonics)	< 0.5% over frequency range
Cross over frequencies (Hz)	250, 1000, 4000
Power handling (music program) watts rms	400
Loudspeaker dimensions	1011mm (H) x 300mm (W) x 460mm (D)
Net weight	32kg



For more details about the GIYA G4 or accessories to compliment, please consult your local specialist retailer, or visit www.vividaudio.com



VIVID audio

Head office & Showroom:
Vivid Audio, 6 Star Road, Partridge Green, West Sussex, RH13 8RA, UK
Tel: +44 (0) 1403 713125 Email: info@vividaudio.com

vividaudio.com



C1
(centre)



V1s
(stand)



V1w
(wall mounted)